## Stratos EcoBase<sup>™</sup>

Specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/10	)"					
Aspect	ISO 2424		Loop pile						
Dye method			Solution dy	red					
Dimension	EN ISO 24342	cm x cm	50 x 50 / 19,68" x 19,68" (20 tiles per box)						
Primary backing	ISO 2424		Polyester fleece						
Secondary backing	ISO 2424		DESSO EcoBase <sup>®</sup> * - Containing on average 80% C2C positively defined recycled content.						
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL <sup>®</sup> (ECONYL <sup>®</sup> is made from 100% regenerated con- tent) **						
Total thickness	ISO 1765	mm	5.5	i	inch	0.2			
Effective pile thickness	ISO 1766	mm	2.5	i	inch	0.10			
Total mass	ISO 8543	g/m²	3900		oz/yd²	115.1			
Total pile mass	ISO 2424	g/m²	550		oz/yd²	16.2			
Effective pile mass	ISO 8543	g/m²	340		oz/yd²	10.0			
Pile density	ISO 8543	g/cm³	0.136		lb/in³	0.0049			-
Number of tufts	ISO 1763	/dm²	1580		/yd²	132104			
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	-						
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		33 Commercial - heavy use						
Luxury rating	EN 1307		LC 1						
Dimensional stability	EN 986	%	≤ 0,20			·			
Impact sound reduction $\Delta L_w$	ISO 10140	dB	24						
Sound absorption	ISO 354	Freq. Hz	125 2	250	500	1000	2000	4000	
		α <sub>s</sub>	0.01 0	0.02	0.07	0.19	0.28	0.32	
Noise reduction	ISO 354	α	0.15						
Thermal resistance	ISO 8302	m².K/W	0.055						
Flammability	EN 13501-1	Bfl - s1 (loose laid tested)							
Prodis - GUT	www.pro-dis.info	)	177B27A8				_		





\* DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® Certified CM Product Standard Version 3.0. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com

\*\* ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

Tarkett's flooring products are to be installed in full accordance with DESSO installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. Tarkett's flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20200401



