

# iD Square

## Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	34 Very Heavy
Technical Characteristics	Norm	Tarkett Value
Total thickness	EN ISO 24346	4,50 mm
Wear layer thickness	EN ISO 24340	0,80 mm
Total weight	EN ISO 23997	5195 g/m <sup>2</sup>
Binder content	EN ISO 10582	Type I
Surface treatment		Top Clean XP
Bevelled edges		No bevel
Installation method		Loose-Lay
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance #	EN 14041	0120-067DoP-2014-11
Technical Performance	Norm	Tarkett Value
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 %
Curly resultant to heat	EN ISO 23999	≤  2  mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual indentation	EN ISO 24343-1	Required value: ≤ 0,10 mm
Furniture leg	EN ISO 16581	No damage
Castor chair	EN ISO 4918	No damage
Impact sound reduction - ΔLw	EN ISO 717-2	15 dB
Reduction of in-room impact noise	NF S31-074	Class B (≤ 75 dB)
Thermal resistance	EN ISO 10456	0,05 m <sup>2</sup> •K/W
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Good resistance
Slip resistance	DIN 51130	R10 R11
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Static Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Underfloor heating		Suitable ( subfloor temperature maximum 27°C)
Sustainability performances	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Recycled content		3 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		12,20 kg CO <sub>2</sub> eq /m <sup>2</sup>
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		6,17 kg CO <sub>2</sub> e /m <sup>2</sup> /year
Total VOC Emissions	EN 16516	Platinum (≤ 10 μg/m <sup>3</sup> )
Dimensions and designs		
Tile	Parallogr.left 1200x200mm - 10 tiles=2 m <sup>2</sup> /box - 48 boxes/pallet Parallogrright 1200x200mm - 10 tiles=2 m <sup>2</sup> /box - 48 boxes/pallet	
Plank	Plank 250 x 1000 mm - 9 planks=2,25 m <sup>2</sup> /box - 48 boxes/pallet Plank 1200x200mm - 10 planks=2,4 m <sup>2</sup> /box - 48 boxes/pallet	
Tile	Tile 50 x 50 cm / 19,68" x 19,68" - 9 tiles=2,25 m <sup>2</sup> /box - 48 boxes/pallet Tile 666 x 666 mm - 5 tiles=2,22 m <sup>2</sup> /box - 26 boxes/pallet Tile 1000 x 1000 mm - 1 Tile=1 m <sup>2</sup> /box - 1 box/pallet	
Number of designs available	50	

Slip resistance DIN : R10/R11 depending on embossing



The above information is subject to modification for the benefit of further improvement (09/12/2022). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for the instructions.